KYOCERA
Document Solutions

> PRINT > COPY > SCAN > FAX

TASKalfa 3212i
TASKalfa 4012i

MONOCHROME MULTIFUNCTION PRODUCT
FOR A4/A3 FORMAT

BRING SEAMLESS EFFICIENCY

- **Fast A4 copy/print speed up to 32/40 cpm.**
- **High image quality with 1,200 x 1,200 dpi print resolution.**
- **Superior scanning performance with dual scan speed up to 160/160 ipm A4 Mono/Color *.**
- **Speedy first copy time in just 3.6 seconds** and warm up time 18 seconds.**
- **320GB*** hard disk capacity and 2GB RAM to meet heavy-duty tasks without an additional hard drive.**
- **Flexible with various paper handling systems and different capacity document processor combinations to meet different users' requirements.**
- **Convenient with inner Job Separator as standard.**
- **Environmentally friendly with low energy consumption due to intelligent device recovery system.**

* Optional DP-7110 required.
** TASKalfa 4012i only.
***Optional for TASKalfa 3212i.

TASKalfa

			Main Specifications	
Model			TASKalfa 3212i	TASKalfa 4012i
Main Function			Copy, Print, Scan, Fax (Optional)	
Writing Method			Semiconductor Laser	
CPU			T1024 (Dual Core) 1.0 GHz	
Print Speed (A4)	Simplex (Mono)		32 ppm	40 ppm
Scanning Speed (A4) 300dpi	DP-7100 (Mono/Color)	Simplex	80/80 ipm	
		Duplex	48/48 ipm	
Scanning Speed (A4) 300dpi Dual Scan	DP-7110 (Mono/Color)	Simplex	80/80 ipm	
		Duplex	160/160 ipm	
Scanning Speed (A4) 300dpi	DP-7120 (Mono/Color)	Simplex	48/48 ipm	
		Duplex	15/15 ipm	
Memory			Standard 2GB (Max. 2GB)	
SSD/HDD Capacity			32GB (Standard)/ 320GB (Optional)	8GB / 320GB (Standard)
Warm Up Time			18 seconds	
Paper Capacity	Standard		2 x 500 sheets (Cassette) + 100 sheets (MPT)	
	Maximum		4,100 sheets (Main Unit + PF-810 + MPT)	
Paper Size	Cassette		Min. A5R - Max. A3 (Ledger)	
	MPT		Min. A6R - Max. A3 (Ledger)	
Paper Weight	Cassette		60 - 163 g/m^2	
	MPT		45 - 256 g/m^2	
Duplex Printing			Paper size: A5R - A3 / Ledger; Paper weight: 60 - 163 g/m^2	
Output Capacity			250 sheets + 50 sheets (with Inner Job Separator) face-down	
Control Panel			9 inch Color Touch LCD Panel	
Dimension (W x D x H) (Main Unit)			594mm x 696mm x 683mm	
Weight (Main Unit)			Approx. 59 kg	
Power Consumption (Standard configuration)	Copy/Print Mode		510W or less	600W or less
	Stand-by Mode		100W or less	
	Energy Saver		1.0W or less	
Noise (ISO7779/ ISO9296)	Copy/Print Mode		66.0dB(A)	67.0dB(A)
	Stand-by Mode		43dB(A)	
			Copy Functions (Standard)	
Copy Size			Max. A3 (Ledger) - Min. A6R	
Resolution			600 x 600 dpi	
First Copy Time			4.3 seconds	3.6 seconds
Zoom Ratio	Manual		25% - 400% (1% Step)	
	Pre-defined		5R5E	
Multiple Copy			1 - 999	
			Print Functions (Standard)	
Resolution			9,600 Equivalent x 600 dpi; 1,200 x 1,200 dpi	
PDL			PRESCRIBE, PCL6 (PCL-5e, PCL-XL), KPDL3 (PostScript 3 compatible), XPS, OpenXPS, PDF Direct Print, PPML	
First Print Out Time			4.9 seconds	4.2 seconds
Supported Protocol			NetBEUI, FTP, Port 9100, LPR, IPP, IPP over SSL, WSD Print	
Operating System Supported			Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Vista, Windows 7, Windows 8, Windows 10; Apple Macintosh OS 10.5 or later; Linux	
Interface			USB2.0 High Speed x1; 1000BASE-T/100BASE-TX/10BASE-T; USB Host interface (USB Host) x4; NFC TAG x1	
USB Memory Printing			Standard	
USB Memory Printing Format			TIFF, JPEG, PDF, XPS	
Mobile Printing			AirPrint, Mopria, KYOCERA Mobile Print	
			Scan Functions (Standard)	
Color Selection			Auto Color (Color/Gray); Auto Color (Color/B&W); Full Color; Grayscale; Black & White	
Resolution			600dpi, 400dpi, 300dpi, 200dpi, 200x100dpi, 200x400dpi	
File Format			TIFF, JPEG, XPS, OpenXPS, PDF (MMR/JPG/High-compression PDF), PDF/A, Searchable PDF (Optional)	
Image Type Mode			Text, Photo, Text + Photo	
Transmission Type			Scan to SMB; Scan to E-mail; Scan to FTP or FTP over SSL; Scan to USB; TWAIN Scan; WSD Scan	
Address Storage			2,000 addresses (Common address list), 500 groups (Group address list)	
			Fax Functions (Optional)	
Original Size			Max. A3 (Ledger) - Min. A5 (Statement)	
Coding Method			MMR, MR, MH, JBIG	
Transmission Speed			33.6 kbps	
Memory			170MB	
G3 FAX/ Network FAX			Yes	
Dual Fax			Yes (Fax System 12 x 2 units required)	
			Consumables & Options	
Toner Kit			TK-7120	TK-7220
Maintenance Kit			MK-7129	
Platen Cover			Platen Cover Type E	
Document Processor			DP-7100: 140 sheets RADF Type; DP-7110: 270 sheets One-path duplex scan Type; DP-7120: 50 sheets RADF Type	
Paper Feeder			PF-791: 500 sheets x2 (A4/Letter); PF-810: 1,500 sheets x2 (A4/Letter)	
Finisher			AK-740: Paper Exit Path for Finisher; DF-7120: 1,000 sheets Finisher; DF-791: 3,000 sheets Finisher; PH-7C: Punch Unit; MT-730(B): 7 bins Mailbox Sorter; SH12: Staple for DF-791; SH-10: Staple for DF-7120	
Fax System			Fax System 12	
Internet FAX			Internet FAX Kit(A)	
Data Security			Data Security Kit(E)	
Card Authentication			Card Authentication Kit(B)	
Gigabit Ethernet Board			IB-50	
Wireless LAN Interface			IB-35 (802.11 b/g/n/Wireless LAN/WiFi Direct)	
Embedded OCR			Scan Extension Kit(A)	
Storage Device			HD-12: HDD 320GB (TASKalfa 3212i only)	
Numeric Key Pad			NK-7100	

KYOCERA
Document Solutions

บริษัท เคียวเซร่า ด็อคคิวเม้นท์ โซลูชั่นส์ (ประเทศไทย) จำกัด
โทร. 0-2586-0333 โทรสาร 0-2586-0278
www.kyoceradocumentsolutions.co.th

*KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

@All rights reserved. Brochure/KDAS/201803/TOMCAT3

KYOCERA Business Partner