

The Powerful Compact Monochrome Printing Solution for Workgroup



- Fast output speed up to 60 pages per minute A4
- 1200 x 1200 dpi resolution
- Network print as standard* and Wireless printing as option
- Standard duplex unit for double-side printing
- Up to 5 paper trays and 2,600 sheets paper capacity in maximum
- Direct PDF Print from USB flash memory device
- Secure print through User Authentication by IC Card or ID/Password login from the Operation Panel
- High Security with SSL encryption
- Compact and Quiet design
- Only toner replacement design with drum yield up to 500,000 prints
- KYOCERA Integrated Solutions for easy device management, cost control and security
- Exceptional low printing cost in the class

* except ECOSYS FS-2100D





Model Name		ECOSYS FS-2100D	ECOSYS FS-2100DN	ECOSYS FS-4100DN	ECOSYS FS-4200DN	ECOSYS FS-4300DN	
General Specifications							
Type	Desktop						
Printing Method	Laser						
Print Speed (A4)	40ppm	40ppm	45ppm	50ppm	60ppm		
First Print Time	9.0 sec or less	9.0 sec or less	9.0 sec or less	9.0 sec or less	9.0 sec or less	9.0 sec or less	
Warm Up Time	15 sec or less	15 sec or less	15 sec or less	20 sec or less	25 sec or less		
Print Resolution	1,200 x 1,200 dpi						
Max. Monthly Duty Cycle	150,000 pages	150,000 pages	200,000 pages	250,000 pages	275,000 pages		
Duplex	Auto						
Power Source	AC 220 - 240 V, 50/60 Hz						
Power Consumption (Standard configuration)	Printing	564W	584W	618W	677W	757W	
	Stand-by	11.5W	12.2W	13.3W	12.8W	13.1W	
Operation Environment	Temperature	10°C - 32.5°C					
	Humidity	15 to 80% RH					
Noise (ISO7779/ISO9296)	Printing	53dB(A)	53dB(A)	54dB(A)	55dB(A)	57dB(A)	
	Stand-by	30dB(A)			30dB(A)		
Dimension (W x D x H) [mm] (Main Unit)	380 x 416 x 285 mm			380 x 416 x 320 mm			
Weight (Main Unit)	13.5 kg			14.6 kg			
Controller							
CPU	750MHz						
PDL	PCL6, PCL5e/PCLXL, PCL5c, PostScript 3						
Memory (Standard/Maximum)	128MB/ 1,152MB	256MB/ 1,280MB					
Standard Interface	USB2.0, e-KUIO, USB-Host x 2	High Speed USB2.0, 10/100 Base-TX/1,000 Base-T, e-KUIO, USB-Host x 2					
Emulations	Line printer, IBM Proprinter X24E, EPSON LQ850 (Host-based)						
Operation Systems	Microsoft Windows XP/ Vista/ 7, Window Server 2003/2008, Mac OS x						
Network	Option	Standard	Standard	Standard	Standard		
Network Authentication	No	Yes	Yes	Yes	Yes		
Paper Handling							
Paper Capacity (80 g/m ²)	Standard: 500 sheets (Cassette) + 100 sheet (Manual Feed Tray) Max. 2600 sheets						
Paper Size	Front Cassette	A4, A5R, B5R, LGL, LTR, OTHER 216 x 356 - 140 x210 (mm)		A4, A5R, B5R, LGL, LTR, OTHER 216 x 356 - 105 x148 (mm)			
	Manual Feed Tray	216 x 356 - 70 x148 (mm)					
Paper Weight	Cassette/ Manual Feed Tray	60 - 120g/m ² / 60 to 220 g/m ²					
Output Capacity	Max. 250 sheets face-down			Max. 500 sheets face-down			
Options							
Paper Feeder	PF-320: 500 sheets x 4 max. PF-315+: 2,000 sheets + Attachment of PF-315+: PB-325						
250 Sheet Face Up Output Tray	Not Available	Not Available	PT-320	PT-320	PT-320		
Card Authentication	Card Authentication Kit (B) / (B) AC						
Data Security	Data Security Kit (E) / (E) AC						
Gigabit Ethernet Board	IB-50 (1 st NIC)	IB-50 (2 nd NIC)	IB-50 (2 nd NIC)	IB-50 (2 nd NIC)	IB-50 (2 nd NIC)		
Wireless Network Interface	IB-51 (1 st NIC)	IB-51 (2 nd NIC)	IB-51 (2 nd NIC)	IB-51 (2 nd NIC)	IB-51 (2 nd NIC)		
Parallel IF: IEEE 1284 Interface Kit	IB-32						
Storage Device: HD-6 (SSD)	32GB						
Consumables							
Toner Kit (Page Yield in accordance with ISO/IEC 19752)	[TK-3104] 12,500 pages		[TK-3114] 15,500 pages	[TK-3134] 25,000 pages			
Capacity of Start Up Toner	6,000 pages		8,000 pages	10,000 pages			
Maintenance Kit	[MK-3104] 300,000 pages		[MK-3134] 600,000 pages				



KYOCERA Document Solutions (Thailand) Corp., Ltd.
335 Ratchadapisek Rd., Wongsawang, Bangsue, Bangkok 10800
Tel. (02) 586-0333 Fax. (02) 586-0278, 910-8710
www.kyoceradocumentsolutions.co.th

*KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

@All rights reserved.

KYOCERA Business Partner

